

LS ANSWER 68 OF 575 CA COPYRIGHT 2004 ACS on STN
 AN 135:348050 CA
 ED Entered STN: 29 Nov 2001
 TI Cement-based hydraulic compositions, fiber-reinforced cured
 hydraulic products, and method for their on-site placing
 IN Takizawa, Kiyoshi; Saito, Tadashi; Ogawa, Atsuhisa; Suemori, Hisashi;
 Yasushiro, Hideki
 PA Kuraray Co., Ltd., Japan
 SO Jpn. Kokai Tokkyo Koho, 6 pp.
 CODEN: JKXXAF

DT Patent
 LA Japanese
 IC ICM C04B028-02
 ICS C04B016-06; C04B111-20
 CC 58-3 (Cement, Concrete, and Related Building Materials)
 Section cross-reference(s): 40

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 2001316157	A2	20011113	JP 2001-36808	20010214
PRAI	JP 2000-58598	A	20000303		

AB The compns. comprise cement-based hydraulic materials contg.
 silica fume, blast-furnace slag, and/or fly ash (C)
 750-1300, aggregates (S) 400-1100, water (W) 270-420 kg/m³, and
 reinforcement fibers having fineness 55-270 dtex and satisfy $2.625 - 0.0075X \leq Y \leq 3.375 - 0.0075X$ and $47Y + W = 253 - 47Y + 293$,
 where $Y = C/S$. Hardened products of the compns. and on-site placing of
 the compns. and the products are also claimed. The products have high
 toughness and resistance to vibration.

ST cement hydraulic product fiber reinforced; vibration
 resistant fiber reinforced mortar; blast furnace slag fiber reinforced
 cement; fly ash fiber reinforced
 cement; silica fume fiber reinforced cement

IT Cement (construction material)
 (Cement-based hydraulic compns., fiber-reinforced cured
 hydraulic products, and method for their on-site placing)

IT Vinal fibers